

Diametro		Spessore mm	Peso tubo liscio kg/m	Identificazione		
nominale pollici	esterno mm			Corrispondente norme API	standard x strong xx strong	n. di schedula
1/8"	10,3	1,73	0,357	5L	STD	40
		2,41	0,462	5L	XS	80
1/4"	13,7	2,24	0,626	5L	STD	40
		3,02	0,804	5L	XS	80
3/8"	17,1	2,31	0,849	5L	STD	40
		3,20	1,100	5L	XS	80
1/2"	21,3	2,77	1,270	5L	STD	40
		3,73	1,620	5L	XS	80
		4,78	1,950	-	-	160
3/4"	26,7	2,87	1,680	5L	STD	40
		3,91	2,190	5L	XS	80
		5,56	2,890	-	-	160
1"	33,4	3,38	2,500	5L	STD	40
		4,55	3,230	5L	XS	80
		6,35	4,230	-	-	160
1 1/4"	42,2	3,56	3,380	5L	STD	40
		4,85	4,470	5L	XS	80
		6,35	5,600	-	-	160
1 1/2"	48,3	3,68	4,050	5L	STD	40
		5,08	5,410	5L	XS	80
		7,14	7,240	-	-	160
2"	60,3	3,91	5,440	5L 5LX	STD	40
		5,54	7,480	5L 5LX	XS	80
		8,74	11,110	-	-	160
		11,07	13,450	5L 5LX	XXS	-
2 1/2"	73,0	5,16	8,620	5L 5LX	STD	40
		7,01	11,410	5L 5LX	XS	80
		9,52	14,910	-	-	160
		14,02	20,410	5L 5LX	XXS	-
3"	88,9	5,49	11,290	5L 5LX	STD	40
		7,62	15,270	5L 5LX	XS	80
		11,13	21,330	-	-	160
		15,24	27,670	5L 5LX	XXS	-
3 1/2"	101,6	5,74	13,570	5L 5LX	STD	40
		8,08	18,630	5L 5LX	XS	80
4"	114,3	6,02	16,070	5L 5LX	STD	40
		8,56	22,310	5L 5LX	XS	80
		11,13	28,300	5L 5LX	-	120
		13,49	33,530	5L 5LX	-	160
		17,12	41,020	5L 5LX	XXS	-
5"	141,3	6,55	21,780	5L	STD	40
		9,52	30,950	5L	XS	80
		12,70	40,280	5L	-	120
		15,88	49,090	5L	-	160
		19,05	57,420	5L	XXS	-

Diametro		Spessore mm	Peso tubo liscio kg/m	Identificazione		
nominale pollici	esterno mm			Corrispondente norme API	standard x strong xx strong	n. di schedula
6	168,3	7,11	28,260	5L	STD	40
		10,97	42,560	5L 5LX	XS	80
		14,27	54,200	5L 5LX	-	120
		18,26	67,550	5L 5LX	-	160
		21,95	79,180	5L	XXS	-
8	219,1	6,35	33,310	5L 5LX	-	20
		7,04	36,790	5L 5LX	-	30
		8,18	42,530	5L 5LX	STD	40
		10,31	53,090	-	-	60
		12,70	64,630	5L 5LX	XS	80
10	273,0	6,35	41,770	5L 5LX	-	20
		7,80	51,000	5L 5LX	-	30
		9,27	60,290	5L 5LX	STD	40
		12,70	81,540	5L 5LX	XS	60
		15,09	95,970	-	-	80
		18,26	114,740	5L 5LX	-	100
12	323,8	6,35	49,720	5L 5LX	-	20
		8,38	65,200	5L 5LX	-	30
		9,52	73,820	5L 5LX	STD	-
		12,70	97,440	5L 5LX	XS	-
		14,27	108,960	5L 5LX	-	60
		17,48	132,010	5L 5LX	-	80
14	355,6	5,33	46,070	5LX	-	10
		7,92	67,940	5L 5LX	-	20
		9,52	81,280	5L 5LX	STD	30
		12,70	107,380	5L 5LX	XS	-
		15,09	126,680	-	-	60
		19,05	158,080	5L 5LX	-	79
		23,83	194,900	-	-	100
16	406,4	6,35	62,630	5L 5LX	-	10
		7,92	77,860	5L 5LX	-	20
		9,52	93,210	5L 5LX	STD	30
		12,70	123,290	5L 5LX	XS	40
		16,66	160,120	-	-	60
		21,44	203,480	-	-	80
18	457,2	6,35	70,590	5L 5LX	-	10
		7,92	87,790	5L 5LX	-	20
		9,52	105,140	5L 5LX	STD	-
		11,13	122,360	5L 5LX	-	30
		12,70	139,190	5L 5LX	XS	-
		14,27	155,910	5L 5LX	-	40
		19,05	205,800	5L 5LX	-	60
		23,83	254,590	-	-	80

Diametro		Spessore mm	Peso tubo liscio kg/m	Identificazione		
nominale pollici	esterno mm			Corrispondente norme API	standard x strong xx strong	n. di schedula
20	508,0	6,35	78,540	5L 5LX	-	10
		9,52	117,070	5L 5LX	STD	20
		12,70	155,100	5L 5LX	XS	30
		15,09	183,370	-	-	40
		20,62	247,850	5L 5LX	-	60
		26,19	311,110	-	-	80
22	558,8	6,35	86,500	5L 5LX	-	10
		9,52	129,010	5L 5LX	STD	20
		12,70	171,010	5L 5LX	XS	30
		22,22	294,040	-	-	60
24	609,6	6,35	94,450	5L 5LX	-	10
		9,52	140,940	5L 5LX	STD	20
		12,70	186,920	5L 5LX	XS	-
		14,27	209,540	5L 5LX	-	30
		17,48	255,140	5L 5LX	-	40
		24,61	355,020	5L 5LX	-	60
26	660,4	7,92	127,500	5L 5LX	-	10
		9,52	152,870	5L 5LX	STD	-
		12,70	202,830	5L 5LX	XS	20
28	711,2	7,92	137,420	5L 5LX	-	10
		9,52	164,800	5L 5LX	STD	-
		12,70	218,730	5L 5LX	XS	20
		15,88	272,180	5L 5LX	-	30
30	762,0	7,92	147,360	5L 5LX	-	10
		9,52	176,730	5L 5LX	STD	-
		12,70	234,640	5L 5LX	XS	20
		15,88	292,060	5L 5LX	-	30
32	812,8	7,92	157,280	5L 5LX	-	10
		9,52	188,660	5L 5LX	STD	-
		12,70	250,550	5L 5LX	XS	20
		15,88	311,950	5L 5LX	-	30
		17,48	342,700	5L 5LX	-	40
34	863,5	8,74	184,180	5LX	-	10
		9,52	200,590	5L 5LX	STD	-
		12,70	266,460	5L 5LX	XS	20
		15,88	331,830	5L 5LX	-	30
		17,48	364,580	5L 5LX	-	40
36	914,4	7,92	177,130	5L 5LX	-	10
		9,52	212,520	5L 5LX	STD	-
		12,70	282,360	5L 5LX	XS	20
		15,88	351,720	5L 5LX	-	30
		19,05	420,560	5L 5LX	-	40